

DUAL HEAD EMERGENCY LIGHT

Catalog#	
Project:	
Fixture Type:	Date:
Note:	

Hit the Tab key or mouse over the page to see all interactive elements.

The Dual Head Emergency Light provides dependable emergency illumination during power outages, ensuring safe visibility in critical areas. It automatically activates when normal power is interrupted, and its adjustable LED heads deliver bright, focused lighting to illuminate escape routes, stairwells, corridors, and exits, supporting safe and efficient evacuation.

FEATURES & BENEFITS

- Innovative, easy installation in minutes
- Two adjustable LED lamp heads delivering 200 lumens (6500K)
- 90 minutes Emergency Operation
- Maintenance-Free NiCad Battery
- Durable 5VA-Rated Flame-Retardant Thermoplastic Housing
- Top, End, or Back Wall/Ceiling Mounting
- Universal J-box mounting pattern.




Model Number	Input Current	Wattage	LED Type	Charging Time	Emergency Run Time
HL-DHEM	0.028A	2W	2x12pcs ultra bright 2835 SMT LED lamp	24 hours	90 Minutes

PRODUCT SUMMARY

CCT 6500K	Input Voltage 120-277 Vac	Battery Type Nickel Cadmium(3.6V)	Housing Material Thermoplastic ABS
Lumens 200lm	Operating Temp. 0°C to +40°C	Warranty 5 Years	No. of Heads 2-Lamp Heads
Dimming No	Discharge Time 90-Minutes	Finish White	Head Shape Square
Input Current 0.02/0.01A	Recharge Time 24 hours	Mounting Wall	

DIMENSIONS



Length (L)
12.11 Inch
Width (W)
4.53 Inch
Height (H)
3.94 Inch

APPLICATIONS

- Commercial Buildings & Offices, Industrial Facilities, Large Public Venues, Hospitality & Healthcare and Retail Centers & Malls.

INCLUDED ACCESSORIES

- Mounting Hardware

PACKAGING DETAILS

Model No.	Product Dimension (LxWxH) (in)	Case Qty (units)	Case Dimension (LxWxH) (in)	Net Weight Product (lbs)	Gross Weight with Packaging (lbs)	Pallet Load
HL-DHEM	12.11 x 4.53 x 3.94	1	16.0 x 12.8 x 9.1	1.3	1.9	-