



Article No	:	
Version	:	10.23
Prepared By	:	
Checked By	:	

K - OD SERIES POST TOP LIGHT

VARIANTS

Wattage	Product Code
75W	KL75SGFXX

This post top luminaire is a sleek, specification gradesolution for lighting pathways, parking areas, gardens and other outdoor spaces. It can be specified in 50W, 75W, 100W & 170W, and is capable of replacing HID fixtures ranging from 175W - 400W. It Can be used efficiently on pathways as well as parking lots or general areas.



FEATURES

- Super Bright LED
- Wet location rated for outdoor use
- Replace HID/MH 150-200W

CONSTRUCTION

- Precision die cast aluminum body with heat sinking across the full module, enabling a long life span
- Fade resistant powder coat finish
- 2-3/8" or 3' post top tenon
- Toughened Glass lens
- Photocell optional



WARRANTY

APPLICATIONS

- Swimming Pool
- Parking Area
- Garden Area
- Pathways
- Mall

(864) 401-8156

sales@krutled.com

111 Preamble Ct, Anderson, SC- 29621, United States.

All rights reserved. Krut LED reserves the right to make changes to specifications and/or discontinue any product at anytime without the notice. Information presented in this document is reliable and accurate, It does not represent any quotation or contact. No liability will be accepted by the contributor by the publisher for any consequences for its use. Reproduction in whole or part is prohibited without prior consent of the copyright owner.

TECH SPECS

Wattage	Lumens (lm)	Efficiency (lm/W)	Distribution	CCT	CRI	Power Factor	Input Voltage
75W	8147	114.5	Type V	3000K	>73	>0.9	100-277VAC, 50/60Hz
75W	8241	115.6	Type V	4000K	>73	>0.9	100-277VAC, 50/60Hz
75W	8335	117.0	Type V	5000K	>73	>0.9	100-277VAC, 50/60Hz
75W	8429	118.1	Type V	5700K	>73	>0.9	100-277VAC, 50/60Hz

DIMENSIONS

