

LED WRAP FIXTURE

Catalog#	
Project:	
Fixture Type:	Date:
Note:	

Hit the Tab key or mouse over the page to see all interactive elements.

The Havells 4ft LED wrap fixture is built for everyday lighting for spaces where reliable lighting matters most. Its durable housing makes it tough in environments while still spreading light evenly and comfortably. On-site selectable from four wattages (17W/24W/31W/38W) and five CCTs (3000K to 6500K), with dimming capability and 0-10V controls. Suitable for dry and damp locations with 50,000 hours life span.

FEATURES & BENEFITS

- High efficacy with the 4' light delivering 5,510 lumens
- Adjustable 5CCT and 4Wattage options for tailored lighting
- Available in three variant sizes: 2ft, 4ft and 8ft
- Rated for 50,000 hours, offering a 5-year warranty



MASTER PACK
WITH 4 INDIVIDUAL PACKED

Model Number	Wattage	Lumens	Efficacy
HL-WA-4MW-5MCCT-25W-2 Feet**	12W/16W/20W/25W	3,625lm	145 lm/W
HL-WA-4MW-5MCCT-38W-4 Feet	17W/24W/31W/38W	5,510lm	145 lm/W
HL-WA-4MW-5MCCT-68W-8 Feet**	42W/47W/53W/68W	9,860lm	145 lm/W

All models feature selectable CCT options: 3000K/3500K/4000K/5000K/6500K

** Marked is Make to Order

PRODUCT SUMMARY

Efficacy

145 lm/W

CCT (Selectable)

3000K/3500K/4000K/5000K/6500K

CRI

80

Beam Angle

110°

Input Voltage

120-277 Vac

Power Factor (PF)

≥0.9

THD

≤20%

Dimming

0-10V standard

Operating Temp.

-20°C to +50°C

Warranty

5 Years

Finish

White

Mounting

Surface

Housing Material

Sheet metal+PC

Lens Type

PC

APPLICATIONS

- Restaurants & Hotels, Hallways & Corridors, Offices & Commercial Spaces, Hospitals & Healthcare Facilities, Schools & Classrooms, Meeting Rooms, Lobbies & Common Areas, Transit Stations, Stairwells & Utility Areas.

Default Parameters	
Wattage	CCT
25W	6500K
38W	6500K
68W	6500K

DLC PRODUCT INFORMATION			
Order ID	DLC Model Number	DLC Source Identifier	Classification
HL-WA-4MW-5MCCT-25W-2 Feet**	On Progress	On Progress	DLC 6.0 Premium
HL-WA-4MW-5MCCT-38W-4 Feet	On Progress	On Progress	DLC 6.0 Premium
HL-WA-4MW-5MCCT-68W-8 Feet**	On Progress	On Progress	DLC 6.0 Premium

PERFORMANCE

			3000K (>80 CRI)		3500K (>80 CRI)		4000K (>80 CRI)		5000K (>80 CRI)		6500K (>80 CRI)	
Model Number		Wattages	Input Current		Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy
HL-WA-4MW-5MCCT-25W-2 Feet**		12W	0.11A@120V/0.05A@277V		1,740lm	145 lm/W	1,740lm	145 lm/W	1,740lm	145 lm/W	1,740lm	145 lm/W
		16W	0.15A@120V/0.06A@277V		2,320lm	145 lm/W	2,320lm	145 lm/W	2,320lm	145 lm/W	2,320lm	145 lm/W
		20W	0.18A@120V/0.08A@277V		2,900lm	145 lm/W	2,900lm	145 lm/W	2,900lm	145 lm/W	2,900lm	145 lm/W
		25W	0.23A@120V/0.10A@277V		3,625lm	145 lm/W	3,625lm	145 lm/W	3,625lm	145 lm/W	3,625lm	145 lm/W
HL-WA-4MW-5MCCT-38W-4 Feet		17W	0.16A@120V/0.07A@277V		2,465lm	145 lm/W	2,465lm	145 lm/W	2,465lm	145 lm/W	2,465lm	145 lm/W
		24W	0.22A@120V/0.10A@277V		3,480lm	145 lm/W	3,480lm	145 lm/W	3,480lm	145 lm/W	3,480lm	145 lm/W
		31W	0.28A@120V/0.12A@277V		4,495lm	145 lm/W	4,495lm	145 lm/W	4,495lm	145 lm/W	4,495lm	145 lm/W
		38W	0.35A@120V/0.15A@277V		5,510lm	145 lm/W	5,510lm	145 lm/W	5,510lm	145 lm/W	5,510lm	145 lm/W
HL-WA-4MW-5MCCT-68W-8 Feet**		42W	0.39A@120V/0.17A@277V		6,090lm	145 lm/W	6,090lm	145 lm/W	6,090lm	145 lm/W	6,090lm	145 lm/W
		47W	0.43A@120V/0.19A@277V		6,815lm	145 lm/W	6,815lm	145 lm/W	6,815lm	145 lm/W	6,815lm	145 lm/W
		53W	0.49A@120V/0.21A@277V		7,685lm	145 lm/W	7,685lm	145 lm/W	7,685lm	145 lm/W	7,685lm	145 lm/W
		68W	0.62A@120V/0.27A@277V		9,860lm	145 lm/W	9,860lm	145 lm/W	9,860lm	145 lm/W	9,860lm	145 lm/W

Remarks: **Marked is Make to Order

PACKAGING DETAILS

Model Number	Product Dimension (LxWxH) (in)	Case Qty (units)	Case Dimension (LxWxH) (in)	Net Weight Product (lbs)	Gross Weight with Packaging (lbs)
HL-WA-4MW-5MCCT-25W-2 Feet**	24.4 × 5.5 × 2.4	-	-	-	-
HL-WA-4MW-5MCCT-38W-4 Feet	47.6 × 5.5 × 2.4	4	49.06 x 10.55 x 6.26	13.24	18.74
HL-WA-4MW-5MCCT-68W-8 Feet**	93.8 × 5.5 × 2.4	-	-	-	-

DIMENSIONS

